

Statistical Machine Learning

Christian Walder

Machine Learning Research Group
CSIRO Data61

and

College of Engineering and Computer Science
The Australian National University

Canberra
Semester One, 2020.

(Many figures from C. M. Bishop, "Pattern Recognition and Machine Learning")



Outlines

Overview
Introduction
Linear Algebra
Probability
Linear Regression 1
Linear Regression 2
Linear Classification 1
Linear Classification 2
Kernel Methods
Sparse Kernel Methods
Mixture Models and EM 1
Mixture Models and EM 2
Neural Networks 1
Neural Networks 2
Principal Component Analysis
Autoencoders
Graphical Models 1
Graphical Models 2
Graphical Models 3
Sampling
Sequential Data 1
Sequential Data 2



Part XXII

Sequential Data 2

A Simple Example

*Maximum Likelihood for
HMM*

*Forward-Backward
HMM*

*Conditional
Independence*

Alpha-Beta HMM

*How to train a HMM
using EM?*

HMM - Viterbi Algorithm

Example of a Hidden Markov Model



Assume Peter and Mary are students in Canberra and Sydney, respectively. Peter is a computer science student and only interested in riding his bicycle, shopping for new computer gadgets, and studying. (Well, he also does other things but because these other activities don't depend on the weather we neglect them here.)

Mary does not know the current weather in Canberra, but knows the general trends of the weather in Canberra. She also knows Peter well enough to know what he does on average on rainy days and also when the skies are blue.

She believes that the weather (rainy or not rainy) follows a given discrete Markov chain. She tries to guess the sequence of weather patterns for a number of days after Peter tells her on the phone what he did in the last days.

A Simple Example

Maximum Likelihood for HMM

Forward-Backward HMM

Conditional Independence

Alpha-Beta HMM

How to train a HMM using EM?

HMM - Viterbi Algorithm



Example of a Hidden Markov Model

Mary uses the following HMM

		<i>rainy</i>	<i>sunny</i>
initial probability		0.2	0.8
transition probability	<i>rainy</i>	0.3	0.7
	<i>sunny</i>	0.4	0.6
emission probability	<i>cycle</i>	0.1	0.6
	<i>shop</i>	0.4	0.3
	<i>study</i>	0.5	0.1

Assume, Peter tells Mary that the list of his activities in the last days was [*'cycle'*, *'shop'*, *'study'*]

- Calculate the probability of this observation sequence.
- Calculate the most probable sequence of hidden states for these observations.

A Simple Example

Maximum Likelihood for HMM

Forward-Backward HMM

Conditional Independence

Alpha-Beta HMM


How to train a HMM using EM?

HMM - Viterbi Algorithm

Hidden Markov Model



- The trellis for the hidden Markov model
- Find the probability of 'cycle', 'shop', 'study'



A Simple Example

Maximum Likelihood for HMM

Forward-Backward HMM

Conditional Independence


Alpha-Beta HMM

How to train a HMM using EM?

HMM - Viterbi Algorithm



- Find the most probable hidden states for 'cycle', 'shop', 'study'



A Simple Example

Maximum Likelihood for HMM

Forward-Backward HMM

Conditional Independence

Alpha-Beta HMM

How to train a HMM using EM?

HMM - Viterbi Algorithm



- Joint probability distribution over both latent and observed variables

$$p(\mathbf{X}, \mathbf{Z} | \theta) = p(\mathbf{z}_1 | \pi) \left[\prod_{n=2}^N p(\mathbf{z}_n | \mathbf{z}_{n-1}, \mathbf{A}) \right] \prod_{m=1}^N p(\mathbf{x}_m | \mathbf{z}_m, \phi)$$

where $\mathbf{X} = (\mathbf{x}_1, \dots, \mathbf{x}_N)$, $\mathbf{Z} = (\mathbf{z}_1, \dots, \mathbf{z}_N)$, and $\theta = \{\pi, \mathbf{A}, \phi\}$.

- Most of the discussion will be independent of the particular choice of emission probabilities (e.g. discrete tables, Gaussians, mixture of Gaussians).

A Simple Example

Maximum Likelihood for HMM

Forward-Backward HMM

Conditional Independence

Alpha-Beta HMM

How to train a HMM using EM?

HMM - Viterbi Algorithm

Maximum Likelihood for HMM



- We have observed a data set $\mathbf{X} = (\mathbf{x}_1, \dots, \mathbf{x}_n)$.
- Assume it came from a HMM with a given structure (number of nodes, form of emission probabilities).
- The likelihood of the data is

$$p(\mathbf{X} | \theta) = \sum_{\mathbf{Z}} p(\mathbf{X}, \mathbf{Z} | \theta)$$

- This joint distribution does not factorise over n (as with the mixture distribution).
- We have N variables, each with K states : K^N terms. Number of terms grows exponentially with the length of the chain.
- But we can use the **conditional independence** of the latent variables to reorder their calculation later.
- Further obstacle to find a closed loop maximum likelihood solution: calculating the emission probabilities for different states \mathbf{z}_n .

A Simple Example

*Maximum Likelihood for
HMM*

*Forward-Backward
HMM*

*Conditional
Independence*

Alpha-Beta HMM

*How to train a HMM
using EM?*

HMM - Viterbi Algorithm

Maximum Likelihood for HMM - EM

- Employ the EM algorithm to find the Maximum Likelihood for HMM.



A Simple Example

*Maximum Likelihood for
HMM*

*Forward-Backward
HMM*

*Conditional
Independence*

Alpha-Beta HMM

*How to train a HMM
using EM?*

HMM - Viterbi Algorithm

Maximum Likelihood for HMM - EM

- Employ the EM algorithm to find the Maximum Likelihood for HMM.
- Start with some initial parameter settings θ^{old} .



A Simple Example

*Maximum Likelihood for
HMM*

*Forward-Backward
HMM*

*Conditional
Independence*

Alpha-Beta HMM

*How to train a HMM
using EM?*

HMM - Viterbi Algorithm

Maximum Likelihood for HMM - EM

- Employ the EM algorithm to find the Maximum Likelihood for HMM.
- Start with some initial parameter settings θ^{old} .
- E-step: Find the posterior distribution of the latent variables $p(\mathbf{Z} | \mathbf{X}, \theta^{\text{old}})$.



A Simple Example

*Maximum Likelihood for
HMM*

*Forward-Backward
HMM*

*Conditional
Independence*

Alpha-Beta HMM

*How to train a HMM
using EM?*

HMM - Viterbi Algorithm



- Employ the EM algorithm to find the Maximum Likelihood for HMM.
- Start with some initial parameter settings θ^{old} .
- E-step: Find the posterior distribution of the latent variables $p(\mathbf{Z} | \mathbf{X}, \theta^{\text{old}})$.
- M-step: Maximise

$$Q(\theta, \theta^{\text{old}}) = \sum_{\mathbf{Z}} p(\mathbf{Z} | \mathbf{X}, \theta^{\text{old}}) \ln p(\mathbf{Z}, \mathbf{X} | \theta)$$

with respect to the parameters $\theta = \{\pi, \mathbf{A}, \phi\}$.

A Simple Example

Maximum Likelihood for HMM

Forward-Backward HMM

Conditional Independence

Alpha-Beta HMM

How to train a HMM using EM?

HMM - Viterbi Algorithm

Maximum Likelihood for HMM - EM



- Denote the marginal posterior distribution of \mathbf{z}_n by $\gamma(\mathbf{z}_n)$, and
- the joint posterior distribution of two successive latent variables by $\xi(\mathbf{z}_{n-1}, \mathbf{z}_n)$

$$\gamma(\mathbf{z}_n) = p(\mathbf{z}_n | \mathbf{X}, \theta^{\text{old}})$$

$$\xi(\mathbf{z}_{n-1}, \mathbf{z}_n) = p(\mathbf{z}_{n-1}, \mathbf{z}_n | \mathbf{X}, \theta^{\text{old}}).$$

- For each step n , $\gamma(\mathbf{z}_n)$ has K nonnegative values which sum to 1.
- For each step n , $\xi(\mathbf{z}_{n-1}, \mathbf{z}_n)$ has $K \times K$ nonnegative values which sum to 1.
- Elements of these vectors are denoted by $\gamma(z_{nk})$ and $\xi(z_{n-1,j}, z_{nk})$ respectively.

A Simple Example

Maximum Likelihood for HMM

Forward-Backward HMM

Conditional Independence

Alpha-Beta HMM

How to train a HMM using EM?

HMM - Viterbi Algorithm

Maximum Likelihood for HMM - EM



- Because the expectation of a binary random variable is the probability that it is one, we get with this notation

$$\gamma(z_{nk}) = \mathbb{E}[z_{nk}] = \sum_{\mathbf{z}_n} \gamma(\mathbf{z}_n) z_{nk}$$

$$\xi(z_{n-1,j}, z_{nk}) = \mathbb{E}[z_{n-1,j} z_{nk}] = \sum_{\mathbf{z}_{n-1}, \mathbf{z}_n} \xi(\mathbf{z}_{n-1}, \mathbf{z}_n) z_{n-1,j} z_{nk}$$

- Putting all together we get

$$Q(\boldsymbol{\theta}, \boldsymbol{\theta}^{\text{old}}) = \sum_{k=1}^K \gamma(z_{1k}) \ln \pi_k + \sum_{n=2}^N \sum_{j=1}^K \sum_{k=1}^K \xi(z_{n-1,j}, z_{nk}) \ln A_{jk} \\ + \sum_{n=1}^N \sum_{k=1}^K \gamma(z_{nk}) \ln p(\mathbf{x}_n | \phi_k).$$

A Simple Example

Maximum Likelihood for HMM

Forward-Backward HMM

Conditional Independence

Alpha-Beta HMM

How to train a HMM using EM?

HMM - Viterbi Algorithm

Maximum Likelihood for HMM - EM



- M-step: Maximising

$$Q(\boldsymbol{\theta}, \boldsymbol{\theta}^{\text{old}}) = \sum_{k=1}^K \gamma(z_{1k}) \ln \pi_k + \sum_{n=2}^N \sum_{j=1}^K \sum_{k=1}^K \xi(z_{n-1,j}, z_{nk}) \ln A_{jk} \\ + \sum_{n=1}^N \sum_{k=1}^K \gamma(z_{nk}) \ln p(\mathbf{x}_n | \phi_k).$$

- results in

$$\pi_k = \frac{\gamma(z_{1k})}{\sum_{j=1}^K \gamma(z_{1j})} \\ A_{jk} = \frac{\sum_{n=2}^N \xi(z_{n-1,j}, z_{nk})}{\sum_{l=1}^K \sum_{n=2}^N \xi(z_{n-1,j}, z_{nl})}$$

A Simple Example

*Maximum Likelihood for
HMM*

*Forward-Backward
HMM*

*Conditional
Independence*

Alpha-Beta HMM

*How to train a HMM
using EM?*

HMM - Viterbi Algorithm



- Still left: Maximising with respect to ϕ .

$$Q(\theta, \theta^{\text{old}}) = \sum_{k=1}^K \gamma(z_{1k}) \ln \pi_k + \sum_{n=2}^N \sum_{j=1}^K \sum_{k=1}^K \xi(z_{n-1,j}, z_{nk}) \ln A_{jk} \\ + \sum_{n=1}^N \sum_{k=1}^K \gamma(z_{nk}) \ln p(\mathbf{x}_n | \phi_k).$$

- But ϕ only appears in the last term, and under the assumption that all the ϕ_k are independent of each other, this term decouples into a sum.
- Then maximise each contribution $\sum_{n=1}^N \gamma(z_{nk}) \ln p(\mathbf{x}_n | \phi_k)$ individually.

A Simple Example

Maximum Likelihood for HMM

Forward-Backward HMM

Conditional Independence

Alpha-Beta HMM

How to train a HMM using EM?

HMM - Viterbi Algorithm



- In the case of Gaussian emission densities

$$p(\mathbf{x} | \phi_k) = \mathcal{N}(\mathbf{x} | \boldsymbol{\mu}_k, \boldsymbol{\Sigma}_k),$$

we get for the maximising parameters for the emission densities

$$\boldsymbol{\mu}_k = \frac{\sum_{n=1}^N \gamma(z_{nk}) \mathbf{x}_n}{\sum_{n=1}^N \gamma(z_{nk})}$$
$$\boldsymbol{\Sigma}_k = \frac{\sum_{n=1}^N \gamma(z_{nk}) (\mathbf{x}_n - \boldsymbol{\mu}_k)(\mathbf{x}_n - \boldsymbol{\mu}_k)^T}{\sum_{n=1}^N \gamma(z_{nk})}.$$

A Simple Example

Maximum Likelihood for HMM

Forward-Backward HMM

Conditional Independence

Alpha-Beta HMM

How to train a HMM using EM?

HMM - Viterbi Algorithm



- Need to **efficiently** evaluate the $\gamma(z_{nk})$ and $\xi(z_{n-1,j}, z_{nk})$.
- The graphical model for the HMM is a **tree**!
- We know we can use a two-stage message passing algorithm to calculate the posterior distribution of the latent variables.
- For HMM this is called the **forward-backward** algorithm (Rabiner, 1989), or **Baum-Welch** algorithm (Baum, 1972).
- Other variants exist, different only in the form of the messages propagated.
- We look at the most widely known, the **alpha-beta** algorithm.

A Simple Example

Maximum Likelihood for HMM

Forward-Backward HMM

Conditional Independence

Alpha-Beta HMM

How to train a HMM using EM?

HMM - Viterbi Algorithm



Conditional Independence for HMM

Given the data $\mathbf{X} = \{\mathbf{x}_1, \dots, \mathbf{x}_N\}$ the following independence relations hold:

$$p(\mathbf{X} | \mathbf{z}_n) = p(\mathbf{x}_1, \dots, \mathbf{x}_n | \mathbf{z}_n) p(\mathbf{x}_{n+1}, \dots, \mathbf{x}_N | \mathbf{z}_n)$$

$$p(\mathbf{x}_1, \dots, \mathbf{x}_{n-1} | \mathbf{x}_n, \mathbf{z}_n) = p(\mathbf{x}_1, \dots, \mathbf{x}_{n-1} | \mathbf{z}_n)$$

$$p(\mathbf{x}_1, \dots, \mathbf{x}_{n-1} | \mathbf{z}_{n-1}, \mathbf{z}_n) = p(\mathbf{x}_1, \dots, \mathbf{x}_{n-1} | \mathbf{z}_{n-1})$$

$$p(\mathbf{x}_{n+1}, \dots, \mathbf{x}_N | \mathbf{z}_n, \mathbf{z}_{n+1}) = p(\mathbf{x}_{n+1}, \dots, \mathbf{x}_N | \mathbf{z}_{n+1})$$


$$p(\mathbf{x}_{n+2}, \dots, \mathbf{x}_N | \mathbf{x}_{n+1}, \mathbf{z}_{n+1}) = p(\mathbf{x}_{n+2}, \dots, \mathbf{x}_N | \mathbf{z}_{n+1})$$

$$p(\mathbf{X} | \mathbf{z}_{n-1}, \mathbf{z}_n) = p(\mathbf{x}_1, \dots, \mathbf{x}_{n-1} | \mathbf{z}_{n-1}) p(\mathbf{x}_n | \mathbf{z}_n)$$

$$p(\mathbf{x}_{n+1}, \dots, \mathbf{x}_N | \mathbf{z}_n)$$

$$p(\mathbf{x}_{N+1} | \mathbf{X}, \mathbf{z}_{N+1}) = p(\mathbf{x}_{N+1} | \mathbf{z}_{N+1})$$

$$p(\mathbf{z}_{n+1} | \mathbf{X}, \mathbf{z}_N) = p(\mathbf{z}_{n+1} | \mathbf{z}_N)$$



A Simple Example

Maximum Likelihood for HMM

Forward-Backward HMM

Conditional Independence

Alpha-Beta HMM

How to train a HMM using EM?

HMM - Viterbi Algorithm


Conditional Independence for HMM - Example



- Let's look at the following independence relation:

$$p(\mathbf{X} | \mathbf{z}_n) = p(\mathbf{x}_1, \dots, \mathbf{x}_n | \mathbf{z}_n) p(\mathbf{x}_{n+1}, \dots, \mathbf{x}_N | \mathbf{z}_n)$$

- Any path from the set $\{\mathbf{x}_1, \dots, \mathbf{x}_n\}$ to the set $\{\mathbf{x}_{n+1}, \dots, \mathbf{x}_N\}$ has to go through \mathbf{z}_n .
- In $p(\mathbf{X} | \mathbf{z}_n)$ the node \mathbf{z}_n is conditioned on (= observed).
- All paths from $\mathbf{x}_1, \dots, \mathbf{x}_{n-1}$ through \mathbf{z}_n to $\mathbf{x}_{n+1}, \dots, \mathbf{x}_N$ are head-tail.
- The path from \mathbf{x}_n through \mathbf{z}_n to \mathbf{z}_{n+1} is tail-tail, so blocked.
- Therefore $\mathbf{x}_1, \dots, \mathbf{x}_n \perp\!\!\!\perp \mathbf{x}_{n+1}, \dots, \mathbf{x}_N | \mathbf{z}_n$.



A Simple Example

Maximum Likelihood for HMM

Forward-Backward HMM

Conditional Independence

Alpha-Beta HMM

How to train a HMM using EM?

HMM - Viterbi Algorithm



- Define the joint probability of observing all data up to step n and having \mathbf{z}_n as latent variable to be

$$\alpha(\mathbf{z}_n) = p(\mathbf{x}_1, \dots, \mathbf{x}_n, \mathbf{z}_n).$$

- Define the probability of all future data given \mathbf{z}_n to be

$$\beta(\mathbf{z}_n) = p(\mathbf{x}_{n+1}, \dots, \mathbf{x}_N | \mathbf{z}_n).$$

- Then it can be shown the following recursions hold

$$\alpha(\mathbf{z}_n) = p(\mathbf{x}_n | \mathbf{z}_n) \sum_{\mathbf{z}_{n-1}} \alpha(\mathbf{z}_{n-1}) p(\mathbf{z}_n | \mathbf{z}_{n-1})$$

$$\alpha(\mathbf{z}_1) = \prod_{k=1}^K \{\pi_k p(\mathbf{x}_1 | \phi_k)\}^{z_{1k}}$$

A Simple Example

*Maximum Likelihood for
HMM*

*Forward-Backward
HMM*

*Conditional
Independence*

Alpha-Beta HMM


*How to train a HMM
using EM?*

HMM - Viterbi Algorithm



- At step n we can **efficiently** calculate $\alpha(\mathbf{z}_n)$ given $\alpha(\mathbf{z}_{n-1})$

$$\alpha(\mathbf{z}_n) = p(\mathbf{x}_n | \mathbf{z}_n) \sum_{\mathbf{z}_{n-1}} \alpha(\mathbf{z}_{n-1}) p(\mathbf{z}_n | \mathbf{z}_{n-1})$$



A Simple Example

Maximum Likelihood for
HMM

Forward-Backward
HMM

Conditional
Independence

Alpha-Beta HMM


How to train a HMM
using EM?

HMM - Viterbi Algorithm



- And for $\beta(\mathbf{z}_n)$ we get the recursion

$$\beta(\mathbf{z}_n) = \sum_{\mathbf{z}_{n+1}} \beta(\mathbf{z}_{n+1}) p(\mathbf{x}_{n+1} | \mathbf{z}_{n+1}) p(\mathbf{z}_{n+1} | \mathbf{z}_n)$$



A Simple Example

Maximum Likelihood for HMM

Forward-Backward HMM

Conditional Independence

Alpha-Beta HMM

How to train a HMM using EM?

HMM - Viterbi Algorithm




Alpha-Beta HMM

- How do we start the β recursion? What is $\beta(\mathbf{z}_N)$?

$$\beta(\mathbf{z}_N) = p(\mathbf{x}_{N+1}, \dots, \mathbf{x}_N | \mathbf{z}_N).$$

- Can be shown the following is consistent with the approach

$$\beta(\mathbf{z}_N) = 1.$$



A Simple Example

Maximum Likelihood for HMM

Forward-Backward HMM

Conditional Independence

Alpha-Beta HMM

How to train a HMM using EM?

HMM - Viterbi Algorithm



- Now we know how to calculate $\alpha(\mathbf{z}_n)$ and $\beta(\mathbf{z}_n)$ for each step.
- What is the probability of the data $p(\mathbf{X})$?
- Use the definition of $\gamma(\mathbf{z}_n)$ and Bayes

$$\gamma(\mathbf{z}_n) = p(\mathbf{z}_n | \mathbf{X}) = \frac{p(\mathbf{X} | \mathbf{z}_n) p(\mathbf{z}_n)}{p(\mathbf{X})} = \frac{p(\mathbf{X}, \mathbf{z}_n)}{p(\mathbf{X})}$$

- and the following conditional independence statement from the graphical model of the HMM

$$p(\mathbf{X} | \mathbf{z}_n) = \underbrace{p(\mathbf{x}_1, \dots, \mathbf{x}_n | \mathbf{z}_n)}_{\alpha(\mathbf{z}_n)/p(\mathbf{z}_n)} \underbrace{p(\mathbf{x}_{n+1}, \dots, \mathbf{x}_N | \mathbf{z}_n)}_{\beta(\mathbf{z}_n)}$$

- and therefore

$$\gamma(\mathbf{z}_n) = \frac{\alpha(\mathbf{z}_n)\beta(\mathbf{z}_n)}{p(\mathbf{X})}$$

A Simple Example

Maximum Likelihood for HMM

Forward-Backward HMM

Conditional Independence

Alpha-Beta HMM

How to train a HMM using EM?

HMM - Viterbi Algorithm



- Marginalising over \mathbf{z}_n results in

$$1 = \sum_{\mathbf{z}_n} \gamma(\mathbf{z}_n) = \frac{\sum_{\mathbf{z}_n} \alpha(\mathbf{z}_n)\beta(\mathbf{z}_n)}{p(\mathbf{X})}$$

and therefore at each step n

$$p(\mathbf{X}) = \sum_{\mathbf{z}_n} \alpha(\mathbf{z}_n)\beta(\mathbf{z}_n)$$

- Most conveniently evaluated at step N where $\beta(\mathbf{z}_N) = 1$ as

$$p(\mathbf{X}) = \sum_{\mathbf{z}_N} \alpha(\mathbf{z}_N).$$

A Simple Example

*Maximum Likelihood for
HMM*

*Forward-Backward
HMM*

*Conditional
Independence*

Alpha-Beta HMM

*How to train a HMM
using EM?*

HMM - Viterbi Algorithm



- Finally, we need to calculate the joint posterior distribution of two successive latent variables by $\xi(\mathbf{z}_{n-1}, \mathbf{z}_n)$ defined by

$$\xi(\mathbf{z}_{n-1}, \mathbf{z}_n) = p(\mathbf{z}_{n-1}, \mathbf{z}_n | \mathbf{X}).$$

- This can be done directly from the α and β values in the form

$$\xi(\mathbf{z}_{n-1}, \mathbf{z}_n) = \frac{\alpha(\mathbf{z}_{n-1}) p(\mathbf{x}_n | \mathbf{z}_n) p(\mathbf{z}_n | \mathbf{z}_{n-1}) \beta(\mathbf{z}_n)}{p(\mathbf{X})}$$

A Simple Example

*Maximum Likelihood for
HMM*

*Forward-Backward
HMM*

*Conditional
Independence*

Alpha-Beta HMM

*How to train a HMM
using EM?*

HMM - Viterbi Algorithm

How to train a HMM using EM?

- 1 Make an initial selection for the parameters θ^{old} where $\theta = \{\pi, \mathbf{A}, \phi\}$. (Often, \mathbf{A} , π initialised uniformly or randomly. The ϕ_k -initialisation depends on the emission distribution; for Gaussians run K -means first and get μ_k and Σ_k from there.)
- 2 (Start of E-step) Run forward recursion to calculate $\alpha(\mathbf{z}_n)$.
- 3 Run backward recursion to calculate $\beta(\mathbf{z}_n)$.
- 4 Calculate $\gamma(\mathbf{z})$ and $\xi(\mathbf{z}_{n-1}, \mathbf{z}_n)$ from $\alpha(\mathbf{z}_n)$ and $\beta(\mathbf{z}_n)$.
- 5 Evaluate the likelihood $p(\mathbf{X})$.
- 6 (Start of M-step) Find a θ^{new} maximising $Q(\theta, \theta^{\text{old}})$. This results in new settings for the parameters π_k, A_{jk} and ϕ_k as described before.
- 7 Iterate until convergence is detected.



A Simple Example

*Maximum Likelihood for
HMM*

*Forward-Backward
HMM*

*Conditional
Independence*

Alpha-Beta HMM

*How to train a HMM
using EM?*

HMM - Viterbi Algorithm



- In order to calculate the likelihood, we need to use the joint probability $p(\mathbf{X}, \mathbf{Z})$ and sum over all possible values of \mathbf{Z} .
- That means, every particular choice of \mathbf{Z} corresponds to one path through the lattice diagram. There are exponentially many !
- Using the alpha-beta algorithm, the exponential cost has been reduced to a linear cost in the length of the model.
- How did we do that?
- Swapping the order of multiplication and summation.

A Simple Example

Maximum Likelihood for HMM

Forward-Backward HMM

Conditional Independence

Alpha-Beta HMM

How to train a HMM using EM?

HMM - Viterbi Algorithm



- Motivation: The latent states can have some meaningful interpretation, e.g. phonemes in a speech recognition system where the observed variables are the acoustic signals.
- Goal: After the system has been trained, find the most probable states of the latent variables for a given sequence of observations.
- Warning: Finding the set of states which are each individually the most probable does NOT solve this problem.

A Simple Example

*Maximum Likelihood for
HMM*

*Forward-Backward
HMM*

*Conditional
Independence*

Alpha-Beta HMM

*How to train a HMM
using EM?*

HMM - Viterbi Algorithm



A Simple Example

Maximum Likelihood for HMM

Forward-Backward HMM

Conditional Independence

Alpha-Beta HMM

How to train a HMM using EM?

HMM - Viterbi Algorithm

HMM - Viterbi Algorithm


- Define $\omega(\mathbf{z}_n) = \max_{\mathbf{z}_1, \dots, \mathbf{z}_{n-1}} \ln p(\mathbf{x}_1, \dots, \mathbf{x}_n, \mathbf{z}_1, \dots, \mathbf{z}_n)$
- From the joint distribution of the HMM given by

$$p(\mathbf{x}_1, \dots, \mathbf{x}_N, \mathbf{z}_1, \dots, \mathbf{z}_N) = p(\mathbf{z}_1) \left[\prod_{n=2}^N p(\mathbf{z}_n | \mathbf{z}_{n-1}) \right] \prod_{n=1}^N p(\mathbf{x}_n | \mathbf{z}_n)$$

the following recursion can be derived

$$\omega(\mathbf{z}_n) = \ln p(\mathbf{x}_n | \mathbf{z}_n) + \max_{\mathbf{z}_{n-1}} \{ \ln p(\mathbf{z}_n | \mathbf{z}_{n-1}) + \omega(\mathbf{z}_{n-1}) \}$$

$$\omega(\mathbf{z}_1) = \ln p(\mathbf{z}_1) + \ln p(\mathbf{x}_1 | \mathbf{z}_1) = \ln p(\mathbf{x}_1, \mathbf{z}_1)$$



HMM - Viterbi Algorithm




- Calculate

$$\omega(\mathbf{z}_n) = \max_{\mathbf{z}_1, \dots, \mathbf{z}_{n-1}} \ln p(\mathbf{x}_1, \dots, \mathbf{x}_n, \mathbf{z}_1, \dots, \mathbf{z}_n)$$

for $n = 1, \dots, N$.

- For each step n remember which is the best transition to go into each state at the next step.
- At step N : Find the state with the highest probability.
- For $n = 1, \dots, N - 1$: Backtrace which transition led to the most probable state and identify from which state it came.



A Simple Example

Maximum Likelihood for HMM

Forward-Backward HMM

Conditional Independence

Alpha-Beta HMM

How to train a HMM using EM?

HMM - Viterbi Algorithm